



2020jbc_all japan_shinjin




Oil Pattern Distance	43	Reverse Brush Drop	33	Oil Per Board	50 ul
Forward Oil Total	16 mL	Reverse Oil Total	11.15 mL	Volume Oil Total	27.15 mL
Tank Configuration	N/A	Tank A Conditioner	curve	Tank B Conditioner	curve

	START	STOP	LOADS	SPEED	TANK	CROSSED	START	END	FEET	T.OIL
1	5L	5R	1	14	A	31	0.0	0.0	0.0	1550
2	7L	7R	2	14	A	54	0.0	3.9	3.9	2700
3	7L	7R	2	18	A	54	3.9	9.0	5.1	2700
4	9L	9R	2	18	A	46	9.0	14.1	5.1	2300
5	10L	10R	3	22	A	63	14.1	23.4	9.3	3150
6	11L	11R	3	22	A	57	23.4	32.7	9.3	2850
7	13L	13R	1	26	A	15	32.7	36.3	3.6	750
8	2L	2R	0	30	A	0	36.3	43.0	6.7	0

	START	STOP	LOADS	SPEED	TANK	CROSSED	START	END	FEET	T.OIL
1	2L	2R	0	30	B	0	43.0	33.0	-10.0	0
2	12L	12R	2	26	B	34	33.0	25.7	-7.3	1700
3	11L	11R	2	22	B	38	25.7	19.5	-6.2	1900
4	9L	9R	1	22	B	23	19.5	16.4	-3.1	1150
5	7L	7R	1	18	B	27	16.4	13.9	-2.5	1350
6	5L	5R	1	18	B	31	13.9	11.4	-2.5	1550
7	3L	3R	2	14	B	70	11.4	7.5	-3.9	3500
8	2L	2R	0	10	B	0	7.5	0.0	-7.5	0

Cleaner Ratio Main Mix NA Forward
Cleaner Ratio Back End Mix NA Reverse
Cleaner Ratio Back End Distance NA Combined
Buffer RPM: 4 = 720 | 3 = 500 | 2 = 200 | 1 = 50



Item	3L-7L:18L-18R	8L-12L:18L-18R	13L-17L:18L-18R	18L-18R:17R-13R	18L-18R:12R-8R	18L-18R:7R-3R
Description	Outside Track:Middle	Middle Track:Middle	Inside Track:Middle	Middle: Inside Track	Middle:Middle Track	Middle:Outside Track
Track Zone Ratio	5.48	1.47	1	1	1.47	5.48

